

# RESINAL WAX

## DRY-BRIGHT HIGH RESISTANCE WAX

RESINAL WAX is metallized wax particularly suitable for the maintenance of tiles, linoleum, rubber, PVC, varnished wood and for the protection of gres and clinker. The product is an emulsion of high quality acrylic polymers which lead to the formation of a protective water-repellent film, also rewashable and resistant to treading and alcohol.

RESINAL WAX is suitable for exteriors too.

Available in the following versions:  
NEUTRAL, LIGHT BROWN e BLACK.



### Application

Clean the surface to be treated and spread homogeneously on it two or three thin layers of RESINAL WAX by the use of a soft wet cloth; wait approx. 30 minutes between each passage.

To remove old layers of RESINAL WAX use the specific waxer remover **NETTAR DUE** (see its TDS).

Coverage: 40/50 m<sup>2</sup>/lt

### Packaging

Bottles 1,00 l or 5,00 l

### Safety rules

FOR PROFESSIONAL USE ONLY. Strictly respect the informations reported on the labels and consult safety data sheets before use.

### Disposing of waste

Dispose not used product and empty containers in accordance of local in force regulations.



#### TOVER S.R.L.

Via Rosa Luxembourg 2/A  
10093 COLLEGNO (TO)  
Tel.: +39-011/7792823  
Fax.: +39-011/7792749  
REG.IMP.TO  
P.IVA 07783540011  
R.E.A. N° 920259  
www.tover.com  
e-mail: info@tover.com

Azienda  
Certificata



UNI EN ISO  
9001:2000  
Cert. N° 393

**WARNING:** The informations reported in the present technical data sheet are for guidance only and they do not hold our responsibility. Adapt the use of our products to the environmental conditions and materials to be treated.  
**REV-1 19-04-2006.** Current Technical Data Sheet replaces the previous one.