




















56 CM INSERTS FOR JOINT-FREE FLOORS

Insert guide

All blades are sold in packs of 10.

Item no.	Tooth Profile	Material laid		Dimensions [mm]				
		Thickness* [mm]	Consumption** [kg/m ²]	Tooth width (A)	Notch width (B)	Tooth height (C)	Angle (D)	
101560	Straight	-	-	-	-	-	-	
101400	A1	0.41	0.41-0.58	0.5	1.5	1.1	55°	
101340	A2	0.4	0.40-0.56	1.3	1.7	1.4	55°	
101410	A3	0.6	0.60-0.84	0.4	1.6	1.5	45°	
101420	A4	0.28	0.28-0.39	0.4	1.1	0.75	55°	
101430	A5	0.24	0.24-0.34	1.45	1.35	1	55°	
101350	B1	0.48	0.48-0.67	2.6	2.4	2	55°	
101440	B2	0.77	0.77-1.07	2	3	2.55	55°	
101450	B3	0.86	0.86-1.20	3.3	3.7	3.25	55°	
101530	B5	0.73	0.73-1.02	14.30	5.70	5.15	55°	
101460	S1	1.21	1.21-1.69	0.1	1.8	2.55	30°	
101470	S2	1.64	1.64-2.29	0.1	4.2	3.35	60°	
101700	3 x 3	1.2	1.20-1.67	0.1	2.4	2.5	55°	
101690	4 x 4	1.55	1.55-2.16	0.1	3.4	3.2	55°	
101650	5 x 5	1.71	1.71-2.38	0.1	4.4	3.5	55°	
101710	6 x 6	2.6	2.60-3.61	0.1	5.7	5.3	55°	
101360	R1	2.18	2.18-3.05	1.5	4	3	0°	 R1
101370	R2	3.33	3.33-4.67	2	4	5	0°	 R2
101660	R3	3.11	3.11-4.35	2.4	6	5	U	 R3

*) Layer thickness can be increased by up to 40% depending on surface

**) Weight stated without additives

 Blades for component products Blades for component products and levelling compound