



Parquet Oil Refresh NEUTRAL

MAINTENANCE OIL FOR PARQUET



FLOOR EXPERTS

Relax. We have it.

Parquet Oil Refresh is a ready to use blend of natural vegetal oils and hard waxes suitable for an easy and fast maintenance of any oil treated surface in interior. Suitable when the wooden floors are locally dull and worn. Innovative waxes lead to a high surface resistance, both mechanical and chemical towards foot traffic and households products.

Tehnical data

<i>Physical characteristics (20°C – 60% R.V.)</i>			
<i>Aspect</i>	Transparent liquid	<i>Specific gravity</i>	0,900 g/cm ³
<i>Ratio & times (20°C – 60% R.V.)</i>			
<i>Spreading time with pad</i>	15 – 20 min	Possible to walk	4 – 5 h
<i>Polishing</i>	12 – 24 h		
<i>Tehnical characteristics (20°C – 60% R.V.)</i>			
<i>Coverage</i>	~ 50 - 60 m ² /lt	<i>Application temperature</i>	> + 10°C
<i>Storage and Labelling</i>			
<i>Storage in original packaging at ambient temperature</i>	12 months	<i>Symbols of risk</i>	None
<i>Packaging</i>	Cans of 1 L	<i>Cleaning tools</i>	Diluyente RMD/91 or Agrosolv

Application

Before applying maintenance oil clean the floor with Parquet Oil Cleaner to remove dirt and grease. Let the floor dry. Stir before use then apply a thin coat of Parquet Oil Refresh with a cloth. Within 15 – 20 minutes spread the product in an uniform way with a polishing machine with a soft pad. To get a brighter aspect, the day after polish with a soft cloth or a polishing machine.

Notes

- ✓ After oil treatment wait for 2 weeks before the first washing with **Parquet Oil Cleaner**
- ✓ Do not apply **Parquet Oil Refresh** on old varnishes, nitro-based sealers or similar
- ✓ Ventilate the room while oiling
- ✓ Drying times can be affected by ambient causes like high R.H. or low temperatures: in these cases the drying is slower
- ✓ For periodical maintenance the application of **Parquet Polisher** is recommended

Safety rules

FOR PROFESSIONAL USE ONLY. Strictly respect the information reported on the labels and consult safety data sheets before use.

N.B.: CLOTHS AND SPONGES SOAKED OF PRODUCT MIGHT TO CATCH FIRE THROUGH AUTO-COMBUSTION. AFTER USE WET THEM WITH A LOT OF WATER, LET THEM DRYING AND DISPOSE THEM IN ACCORDANCE OF LOCAL FORCE REGULATION.

Disposing of waste

Dispose not used product and empty containers in accordance of local in force regulations.

WARNING: The information reported in present technical data sheet are for guidance only and they do not hold our responsibility; the environmental conditions and the employ modalities are out of our control. We advice to check that the product fits for the work to be done.
REV.2 21-11-2012. Current Technical Data Sheet replaces the previous one.