

TOVCOL S/R

TWO-COMPONENT POLYURETHANE ADESIVE FOR SMALL REPAIRS

TOVCOL S/R is a two-component polyurethane adhesive extra fast drying, especially fitting for fast glueing and repair of timber floors on all kinds on subfloors, allowing any smoothing or sanding work to be done quickly. It is water free and solvent free.



Technical data

Chemical-Physical characteristics (20°C – 60% R.H.)			
Comp A appearance	Thick paste	Specific gravity	1,520 g/cm ³
Comp B appearance	Liquid		

Mixing ratios & Times (20°C – 60% U.R.)			
Mixing ratio	A+B: 90+10 wt	Ready for foot traffic	1 h
Pot-life	5'	Polishing	1 h
Time for adjustments	40'		

Technical characteristics (20°C – 60% U.R.)			
Consumption (10 mm notched trowel)	1000 – 1400 gr/m ²	Application temp.	> 10°C
Shear strenght	> 3 N/mm ²		

Storage & Labeling			
Storage (original unopened packaging stored in normal conditions)	12 months	Symbols of danger	Comp. B: Xn

Cleaning tools	Just before use use alcohol or SOLVENTE DI LAVAGGIO S/23 .
-----------------------	---

Packaging	Bucket gr. 900 + Bottle 100ml
Colours	Light woods (YELLOW PLUG) Dark woods (BROWN PLUG)

Application

Pour B component into the buckets of the A component and mix carefully using an electrical mixer to obtain an homogeneous paste. Use a notched trowel to apply the adhesive on the subfloor that must to be compact, free from dust, sand, lime and oil.

N.B. We advise to not wet the sides of the wooden strips using the TOVCOL S/R; this kind of operation does not allow the natural wood movements inducing cracking and fissuring in time. We recommend instead to wet shorter sides of the wooden strips using the specific vinyl adhesive TOVCOL S (see the relative technical data sheet)

Not enough coherent or dusting concrete substrates have to be first consolidated with one of the primers **PRIMER PU100**, **TOVERFIX**, **ADEBLOK T19** or **PRIMER TS**. In case of wet concrete substrates or in presence of residual moisture content use **PRIMER PU100**, **TOVERFIX**, **ADEBLOK T19** or **IDROBLOK C3** (see relative technical data sheets).

Particularly smooth surfaces (ex. ceramic) must to be made rough (for example by mechanical action) and must to be carefully cleaned to remove in particular the greasy; than apply the specific adhesion promoter **P.EP.P.** (see relative technical data sheet).

Notes

- ✓ Laying prefinished parquet, the exceeding leaked adhesive, still fresh, can be cleaned using the product STRIPCOLL
- ✓ The laying has to be done quickly because of the very fast reaction between the two components.



TOVER S.R.L.
Via Rosa Luxembourg 2/A
10093 COLLEGNO (TO)
Tel.: +39-011/7792823
Fax.: +39-011/7792749
REG.IMP.TO
P.IVA 07783540011
R.E.A. N° 920259
www.tover.com
e-mail: info@tover.com

Azienda
Certificata

UNI EN ISO
9001:2000
Cert. N° 393

- ✓ For an easier and better hands cleaning it is advised to use the specific damp clothes TOVCLEAN.

Safety Rules

FOR PROFESSIONAL USE ONLY. Strictly respect the informations reported on the labels and consult safety data sheets before use.

Disposing of waste

Dispose not used product and empty containers in accordance of local in force regulations.



TOVER S.R.L.
Via Rosa Luxembourg 2/A
10093 COLLEGNO (TO)
Tel.: +39-011/7792823
Fax.: +39-011/7792749
REG.IMP.TO
P.IVA 07783540011
R.E.A. N° 920259
www.tover.com
e-mail: info@tover.com

Azienda
Certificata



UNI EN ISO
9001:2000
Cert. N° 393

WARNING: The informations reported in present technical data sheet are for guidance only and they do not hold our responsibility. Adapt the use of our products to the environmental conditions and materials to be treated.
REV-4 07-04-2009. Current Technical Data Sheet replaces the previous one.