

ARBORITEC™

Refresher

Modern Maintenance for Finished Floors

 **MADE IN SWEDEN**



PLEASE READ ALL INSTRUCTIONS AND SAFETY DATA SHEET BEFORE USING.



Refresher

PRODUCT DESCRIPTION

Arboritec™ Refresher is a modern maintenance product for lacquered wood floor surfaces. Refresher can also be used on laminate, vinyl, PVC or linoleum. It dissolves itself with each new application and does not build up layers. Refresher contains lacquer particles and it prevents the floor from visual signs of aging and wear. Maintenance with Refresher is recommended after every 5th cleaning

DIRECTIONS FOR USE

Recommended working temperature is between 13°C (55°F) and 25°C (77°F). Clean with Arboritec Cleaner. The floor must be free from contamination and dust. Any residual polish or grease must be carefully removed with Arboritec Polish Remover and a sanding screen grit 120. Floors which previously have been treated with polish or wax have to be deep cleaned before using Refresher. Pour Arboritec Refresher directly onto the floor from the can. Do not dilute Refresher. Disperse Refresher with a clean, damp mop or lint-free cloth. Let it dry for about 1 hour. After that the floor is ready to use. If streaks appear it is likely that the floor has been treated with polish or wax. In that case it has to be deep cleaned with suitable polish/ wax remover.

FREQUENCY OF USE

To maintain the look and the protective properties of the lacquer, we recommend an application of Arboritec Refresher after every fifth clean with Arboritec Cleaner.

TECHNICAL DATA

SHAKE VIGOROUSLY



VOC	0 g /l (EU limit value for this product (cat. A/i): 140 g/l (2010) 2004/42/CE)
Content	Copolymer-Acrylate; Ammoniac solution.
Solid content	4%
pH	8,5
Coverage	60 m ² /l
Recommended Use	For maintenance and cleaning of different floor types.
Odour	Very light, non-offending
Drying time	Approx. 1 hour.
Safety/Toxicity	Non-hazardous / Not classified
Packaging	1 litre plastic cans
Storage and transport	Best before 12 months at 5°C to 25°C in unopened package. Protect from frost.
Shelf life	See expiration date on canister.
Chemical Resistance	Resistant to grease, water and ordinary household cleaners and detergents.
Cleaning of tools	Clean tools with water, before the refresher has dried.
Disposal	Dispose it in accordance to local regulations.
Maintenance	Dry cleaning is recommended on all oiled surfaces. If necessary clean with Arboritec Cleaner. Do not leave water on the floor. If the floor is heavily worn, maintain with Arboritec Satin Maintenance Oil.

Safety data sheet is available for download at www.arboritec.com

For technical advice: Contact your distributor or
- **Arboritec AB** technical service at +46 303 56330
- **Arboritec USA Inc.** technical service at +1 303 773 7143

Issued by Arboritec AB - Olof Wiksväg 9, 44465 Jörlanda, Sweden

Arboritec AB
Olof Wiksväg 9
44465 Jörlanda, Sweden
+46 303 56330

Arboritec USA Inc.
8400 E. Crescent Parkway, Suite 600
Greenwood Village, CO 80111, USA
+1 303 773 7143

There are no express or implied warranties, including warranties of merchantability and/or fitness for a particular purpose. Buyers' remedies are limited to replacement or refund of the purchase price. Manufacturer assumes no liability for injuries, incidental or consequential damages. User shall determine suitability of product for intended use.

The information and recommendations in this data sheet are guidelines for application and are not to be construed as a guarantee. In all cases it is the responsibility of the user to determine if the product is suitable for the purpose, and complete a successful application. Arboritec can only guarantee the delivered product. If the user is in doubt we would recommend a preliminary onsite test. Please ensure you have read and understood all information on the labels and in the safety data sheets before using this product.

This data sheet replaces all previous versions.

Ver. 12.2018