

# 10-ABCD-156-RIESLING



# Size **Board**

LENGTH	1150 mm
WIDTH	156 mm
TOTAL THICKNESS	10 mm
THICKNESS TOP LAYER	2.5 mm

## Size **Pack**

PACK LENGTH	1160 mm
PACK WIDTH	166 mm
PACK THICKNESS	100 mm
PACK WEIGHT	17 kg
LAYERS/PACK	9
M²/PACK	1.61 m <sup>2</sup>

## Size **Pallet**

LENGTH PALLET	1180 mm
WIDTH PALLET	1190 mm
HEIGHT PALLET	720 mm
WEIGHT PALLET	930 kg
PACKS/PALLET	54
M <sup>2</sup> /PALLET	86.94 m <sup>2</sup>

#### **Characteristics**

## Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	ABCD
CONSTRUCTION	3-layer
THICKNESS TOP LAYER	2.5 mm
STRIPS	1 strip
CUTTING METHOD	Sawn veneer
BEVEL	Micro bevel Four sides (0,50 mm)
COLOUR FINISH	Natural lacquer
SURFACE STRUCTURE	Smooth

# Composition of the support

SUPPORT TYPE	HDF + Birch support and backing
WOOD SPECIES SUPPORT	Birch
SUPPORT CONSTRUCTION	HDF ( 2 layer)
TOTAL THICKNESS SUPPORT	8.5 mm
ADHESION	Crosswise (Casco)


# Installation

SYSTEM APPLICATIONS UNDERFLOOR HEATING

Click system Light household use No

Normal household use RESANDABLE

Resandable



# 10-ABCD-156-RIESLING

© This fact sheet was written by Labeco BVBA, Warandestraat 37-39, B-9810 NAZARETH. Text, photographs, drawings, tables, graphs should in no way be distributed, used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables, graphs used in this sheet are intended only as illustrations. No rights can be derived from them.