

AUDION Packaging Machines

Together we make the perfect package



D 552 Bandsealers

D552 horizontal & vertical bandsealers



D552 AH Horizontal bandsealer: Bags are sealed laying flat.

D 552 AH band sealer continuously seals bags lying flat, for applications requiring speed and convenience.

The sealing unit is adjustable in height and can also be tilted up to 30° to keep free flowing products in the bag. The conveyor unit can also be adjusted in height by 35mm separately from the sealing unit. For longer product, the conveyor frame can be pulled out by 70mm.

All operating parameters are controlled by a digital control panel, including an automatic cool down function. By using PTFE seal belts; polyethylene, polypropylene, cellophane, paper, aluminium and other laminates can be sealed. The maximum distance between the seal and the top of the bag is 40 mm.

Options: Code seal, stainless steel construction



D552 AVT Vertical bandsealer: Bags are sealed in upright position.

D 552 AVT is a vertical band sealer, designed for large pre-made bags that are sealed standing up.

It is ideal for powder, liquid, or solid products that would spill if sealed lying flat. The sealing head on the D 552 AVT can be rotated 90°C, from vertical to horizontal, and is also adjustable in height. The D 552 AVT has the same easy-to-operate digital control panel and PTFE seal belts as the D 552 AH. The D 552 AVT is equipped with a height-adjustable integrated conveyor belt. The speed of this conveyor can be synchronized to the sealing unit from the control panel.

Options: code seal, stainless steel construction

Technical Specifications D552 AH	
Seal width	10 mm
Operating speed	Variable up to 10 m/min
Conveyor belt width	250 mm
Conveyor belt height	Adjustable range 35 mm
Conveyor belt horizontal position	Adjustable range 70 mm
Power	1100 W
Voltage	230V
Dimensions	1350 x 610 x 1030-1230 mm
Weight	93 kg

Technical Specifications D552 AVT	
Seal width	10 mm
Operating speed	Variable up to 10 m/min
Conveyor belt width	250 mm
Conveyor belt height	Adjustable in 11 positions within 500 mm range
Conveyor belt horizontal position	Adjustable within 90 mm range
Power	1200 W
Voltage	230V
Dimensions	1410 x 610 x 1440 mm
Weight	126 kg