

PHOTOCENTRIC 3D RESIN (Castable)

Page: 1

Compilation date: 22/02/2017

**Revision No: 2** 

## Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: PHOTOCENTRIC 3D DAYLIGHT RESIN (CASTABLE)

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

## 1.3. Details of the supplier of the safety data sheet

Use of substance / mixture: PC30: Photo-chemicals for 3D printing.

Company name: Photocentric Ltd

Cambridge House

Oxney Road
Peterborough
Cambridgeshire

PE1 5YW

England

**Tel:** +44 (0) 1733 349937 **Email:** <u>info@photocentric.co.uk</u>

## 1.4. Emergency telephone number

**Emergency tel:** +44 (0) 1733 349937

(office hours only)

# Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1A: H317; STOT

SE 3: H335

Most important adverse effects: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

May cause respiratory irritation. Harmful to aquatic life with long lasting effects.

## 2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS07: Exclamation mark





PHOTOCENTRIC 3D RESIN (Castable)

Page: 2

Signal words: Warning

Precautionary statements: P280: W ear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: W ash with plenty of water/soap and water.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.
P312: Call a POISON CENTER/doctor if you feel unwell.
P321: Specific treatment (see instructions on this label).

#### 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

#### 3.2. Mixtures

## Hazardous ingredients:

#### BISPHENOL A ETHOXYLATE DIMETHACRYLATE

EINECS	CAS	PBT / W EL	CLP Classification	Percent
-	Proprietary	-	Skin Irrit. 2: H315; Skin Sens. 1A: H317; Eye Irrit. 2: H319; STOT SE 3: H335	50-70%
DIACRYLATE				
-	Proprietary	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317	10-30%
ACRYLATE				
-	Proprietary	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319	1-10%
ACRYLATE				
-	Proprietary	-	Eye Irrit. 2: H319	1-10%
ACRYLATE				
-	Proprietary	-	Acute Tox. 4: H302; Skin Sens. 1A: H317; Aquatic Chronic 1: H410	1-10%
PHOTOINITIA	TOR			
-	Proprietary	-	Flam. Sol. 1: H228; Repr. 2: H361f; STOT RE 2: H373; Aquatic Chronic 2: H411	1-1.5%

#### Section 4: First aid measures

## 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.



PHOTOCENTRIC 3D RESIN (Castable)

Page: 3

Ingestion: W ash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

# 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

## 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. W ear protective clothing to prevent contact with skin and eyes.

# Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

## 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.



PHOTOCENTRIC 3D RESIN (Castable)

## Section 7: Handling and storage

Page: 4

## 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

## 7.2. Conditions for safe storage, including any incompatibilities

#### 7.3. Specific end use(s)

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Specific end use(s): No data available.

# Section 8: Exposure controls/personal protection

## 8.1. Control parameters

Workplace exposure limits: No data available.

#### **DNEL/PNEC Values**

#### 8.2. Exposure controls

**DNEL / PNEC** No data available.

**Engineering measures:** Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

# Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Various colours

Odour: Characteristic odour

Evaporation rate: Negligible

Oxidising: No data available.

**Solubility in water:** No data available.

Also soluble in: Most organic solvents.

Viscosity: Viscous

Kinematic viscosity: 200-300cPs

Viscosity test method: Brookfield Spindle L2 @ 25 C

Boiling point/range°C: No data available. Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: >93 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Relative density: No data available.

pH: No data available.



PHOTOCENTRIC 3D RESIN (Castable)

Page: 5

VOC g/I: No data available.

#### 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

## 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

## 10.3. Possibility of hazardous reactions

Chemical stability: Stable under normal conditions.

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat.

#### 10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

## **Section 11: Toxicological information**

### 11.1. Information on toxicological effects

# Hazardous ingredients:

## DIACRYLATE

IPR	RAT	LD50	760	mg/kg
ORL	RAT	LD50	5	gm/kg

## Relevant hazards for product:

Hazard	Route	Basis	
Skin corrosion/irritation	DRM	Hazardous: calculated	
Serious eye damage/irritation	OPT	Hazardous: calculated	
Respiratory/skin sensitisation	-	Hazardous: calculated	
STOT-single exposure	INH	Hazardous: calculated	

# Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.



PHOTOCENTRIC 3D RESIN (Castable)

Page: 6

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

### **Section 12: Ecological information**

#### 12.1. Toxicity

Ecotoxicity values: No data available.

#### 12.2. Persistence and degradability

## 12.3. Bioaccumulative potential

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

## 12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

Mobility: Readily absorbed into soil.

PBT identification: This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

### Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

# Section 14: Transport information

Transport class: This product does not require a classification for transport.

# **Section 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

### **Section 16: Other information**

## PHOTOCENTRIC 3D RESIN (Castable)

Page: 7

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H228: Flammable solid.

H302: Harmful if swallowed.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H361f: Suspected of damaging fertility.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]