



Sicad s.p.A.

Via Caduti della Liberazione, 57
21040 Uboldo (VA) – Italia
Tel: +39 02 964121 Fax: +39 02 96412294
Web: www.eurocel.it

PRODUCT INFORMATION

EUROCEL MSK 180

DESCRIPTION

Polyester masking tape for powder coating.

PRODUCT DATA

Backing	0.050 mm PET film
Adhesive	Siliconic

	Unit	Value	Method
Total thickness	mm	0.093	PSTC 133
Adhesion to steel	N/25mm	10	PSTC 101
Tensile strength MD	N/25mm	250	PSTC 131
Elongation at break	%	140	PSTC 131
Temp. Resistance	°C	190°C	=

APPLICATION

High temperature green masking tape suitable for powder coating.

Features	Benefits	
Siliconic adhesive	<ul style="list-style-type: none"> ✓ Good adhesion level ✓ High thermal resistance 	<ul style="list-style-type: none"> ✓ No adhesive residue after removal
Polyester backing	<ul style="list-style-type: none"> ✓ Excellent mechanical resistance 	<ul style="list-style-type: none"> ✓ Easy handling

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

MK014EN_REV02_MSK180

Società Italiana Cellophane Adesivo
P.I. e C.F. IT 00220060123
Iscrizione R.E.A. Varese n. 129175
Reg. Imprese Varese n. 00220060123
Capitale Sociale € 15.000.000 i.v.