


**ECE316V4PU**

|  |                    |                       |
|--|--------------------|-----------------------|
| <b>Operating Current</b>                     |                    | 16A                   |
| <b>Product</b>                               |                    | CEE Norm              |
| <b>Type</b>                                  |                    | Extension Type Socket |
| <b>Contact</b>                               |                    | 2+Neutral             |
| <b>Mechanical Life</b>                       | <b>Min Qty</b>     | ≥ 500                 |
| <b>Electrical Life</b>                       | <b>Min Qty</b>     | ≥ 100                 |
| <b>Operating Frequency</b>                   | <b>On-Off/Hour</b> | Mech.240 Elec.120     |
| <b>Insulation Voltage</b>                    | <b>Ui</b>          | 690V                  |
| <b>Impulse Withstand Voltage</b>             | <b>Uimp</b>        | 6 kV                  |
| <b>Dielectric Strength (Body-Contact)</b>    |                    | 1890V AC              |
| <b>Dielectric Strength (Contact-Contact)</b> |                    | 3000V AC              |
| <b>Isolation Resistance</b>                  |                    | 10 MΩ Min. (500 V DC) |
| <b>Operating Temperature</b>                 |                    | -40 / +125 °C         |
| <b>Pollution Degree</b>                      |                    | 2                     |
| <b>Body Material</b>                         |                    | Plastic               |
| <b>Production Time</b>                       |                    | 2020                  |
| <b>Serial</b>                                |                    | ECE Series            |

