

GPA Series power terminal blocks

with UL94V-0 polyamide insulating body

- mounting for both PR/DIN and PR/3 rails which meet IEC 60715 norms, "G32" and TH/35 types
- panel mount version - M6 screws (recommended with screwdriver and washer slot)
- nominal voltage 1000 V
- possibility of compacting the terminal blocks using M3 threaded stay bolts
- maximum continual operating temperature 100°C



grey version	GPA.150/GR Cat. No. GA200GR	GPA.240/GR Cat. No. GA300GR
beige version	GPA.150 Cat. No. GA200	GPA.240 Cat. No. GA300
grey panel-mount version	GPA.150/FX/GR Cat. No. GF200GR	GPA.240/FX/GR Cat. No. GF300GR
beige panel-mount version	GPA.150/FIX Cat. No. GF200	GPA.240/FIX Cat. No. GF300
TECHNICAL CHARACTERISTICS		
function/type		
rated cross-section (mm ²)		
connecting capacity		
flexible (mm ²)		
rigid (mm ²)		
bars and/or cable lugs		
rated voltage / rated current / gauge conf. to IEC 60947-7-1		
rated voltage / rated current / AWG / tightening torque value UL		
rated impulse withstand voltage / pollution degree		
insulation stripping length (mm)		
tightening torque value - bar (test / recommended) (Nm)		
tightening torque value - cable (test / recommended) (Nm)		
height / width / thickness TH/35 7.5 mm		
height / width / thickness TH/35 15 mm		
height / width / thickness G32		
height / width (fixing distance between centres) / thickness (panel mount)		
feed-through 150		
feed-through 240		
95 – 240		
50 – 300		
1000 V / 309 A / B14		
600 V / 309 A / 1/0 AWG str. – 350		
MCM str. / 142 lb.in.		
12 KV / 3		
35		
10 / 15 (Allen screw, 5 mm wrench)		
99 / 108 / 31		
106 / 108 / 31		
103 / 108 / 31		
94 / 122 (106) / 31		
1000 V / 415 A / B16		
600 V / 415 A / 3/0 AWG str. – 600		
MCM str. / 300 lb.in.		
12 KV / 3		
40		
14 / 21 (Allen screw, 6 mm wrench)		
120 / 119 / 37		
128 / 119 / 37		
124 / 119 / 37		
115 / 134 (118) / 37		

APPROVALS



ACCESSORIES		Type	Cat. No.	Type	Cat. No.
End sections	grey beige	-	-	-	-
Permanent cross connection		-	-	-	-
Rated current carrying capacity of jumper (A)		-	-	-	-
Multiple common bar 250 mm		-	-	-	-
Shunting screw and sleeve		-	-	-	-
Coloured partition red, green, white		-	-	-	-
Cross connection barrier red		-	-	-	-
Test plug socket		-	-	-	-
Test plug		-	-	-	-
Numbering strip		-	-	-	-
Cover for cross-connection		-	-	-	-
Mounting rail support flat for PR/DIN and PR/3	Z121213	Z121213	ACI121213	Z121213	Z121213
sloped for PR/DIN and PR/3	ACI121024	Z121024	ACI121024	Z121024	Z121024
printed or blank	CNU/8/51	NU0851	CNU/8/51	NU0851	NU0851
End bracket	BTU for PR/DIN and PR/3	BT005	BTU for PR/DIN and PR/3	BT005	BT005
	CDA/BT for PR/DIN only	CD003	CDA/BT for PR/DIN only	CD003	CD003
	BT/3-BTO for PR/3 only	BT003-BT007	BT/3-BTO for PR/3 only	BT003-BT007	BT003-BT007