


Diode-holders

- for 1 A diodes (types 1N4001 – 1N4007)
- for 3 A diodes (type BY 255)
- universal mounting for both PR/DIN and PR/3 rails which meet IEC 60715 norms, "G32" and TH/35 types
- available in grey and beige
- maximum operating temperature 100°C



The terminal block is fitted with a disconnection lever with hole (**) provided for possible sealing of the knife or for inserting a pawl for moving simultaneously several contiguous knives



The terminal block is fitted with a disconnection lever with hole (**) provided for possible sealing of the knife or for inserting a pawl for moving simultaneously several contiguous knives

The SFR/1A or SFR/3A insert is provided as an accessory and must be mounted in the lever of the SFR.4 basic terminal block, to transform it into a diode holder

(*) value referred to the insulation characteristics of the terminal block

The /GR tag indicates the grey version.

grey version
beige version

SFR.4/GR	Cat. No. SF900GR
SFR.4	Cat. No. SF900

SFR.4/D1/GR	Cat. No. SF901GR
complete with diode 1N4001	
SFR.4/D3/GR	Cat. No. SF903GR
complete with diode 1N4007	
SFR.4/D1	Cat. No. SFR901
complete with diode 1N4001	
SFR.4/D3	Cat. No. SFR903
complete with diode 1N4007	

TECHNICAL CHARACTERISTICS	
function/type	
rated cross-section (mm ²)	
connecting capacity	
flexible (mm ²)	
rigid (mm ²)	
max. flexible with ferrule (mm ²) - ferrule type	
rated voltage / rated current / gauge	conf. to IEC 60947-7-1
rated voltage / rated current / AWG / tightening torque value	UL
(Ex e) rated voltage	(V)
rated impulse withstand voltage / pollution degree	
insulation stripping length (mm)	
tightening torque value (test / max) (Nm)	
height / width / thickness	TH/35 7.5 mm
height / width / thickness	TH/35 15 mm
height / width / thickness	G32

	for 1 A or 3 A diodes
	4
	0.2-6
	0.2-6
	4-WP40/16
	800 V (*) / 1 (3) A / A4
	-
	6 KV (*) / 3
	11
	0.5 / 1.2
	52 / 52 / 8
	60 / 52 / 8
	56 / 52 / 8

	with 1 A or 3 A diode
	4
	0.2-6
	0.2-6
	4-WP40/16
	800 V (*) / 1 (3) A / A4
	-
	6 KV (*) / 3
	11
	0.5 / 1.2
	52 / 52 / 8
	60 / 52 / 8
	56 / 52 / 8

APPROVALS



ACCESSORIES	
End sections	grey beige blue
Permanent cross connection	
Switchable cross connection	
Multiple common bar	250 mm
Shunting screw and sleeve	
Coloured partition	red, green, white
Cross connection barrier	red
Test plug socket	
Test plug	
Numbering strip	
Miniature fuse	
Conducting element	
Cartridge / insert with 1 A diode	
Cartridge / insert with 3 A diode	
Marking tag	printed or blank
End bracket	

Type	Cat. No.
SFR/PT/GR	SF701GR
SFR/PT	SF701
SFR/PT (Ex)i	SF801
-	-
-	-
-	-
DFU/3	DU03..
-	-
-	-
SFR/11A (with 1 A diode)	SF992
SFR/13A (with 3 A diode)	SF993
CNU/8/51	NU0851
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BTO for PR/3 only	BT003-BT007

Type	Cat. No.
SFR/PT/GR	SF701GR
SFR/PT	SF701
SFR/PT (Ex)i	SF801
-	-
-	-
-	-
DFU/3	DU03..
-	-
-	-
F5	FN...
-	-
SFR/11A (with 1 A diode)	SF992
SFR/13A (with 3 A diode)	SF993
CNU/8/51	NU0851
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BTO for PR/3 only	BT003-BT007