

LED SMD προβολέας με αισθητήρα κίνησης / LED SMD flood luminaire with motion sensor "X"

30.000Hrs

IP66

2 Έτη εγγύηση
2 years guarantee



German Design

Slim Design




X10**S

"X" 10W 120° 230V

ΓΕΝ. ΣΥΣΚΕΥΑΣΙΑ
MASTER PACKING

X1030S 3000K 800Lm	24
X1040S 4000K 840Lm	24
X1060S 6000K 890Lm	24




X20**S

"X" 20W 120° 230V

ΓΕΝ. ΣΥΣΚΕΥΑΣΙΑ
MASTER PACKING

X2030S 3000K 1600Lm	12
X2040S 4000K 1660Lm	12
X2060S 6000K 1700Lm	12




X30**S

"X" 30W 120° 230V

ΓΕΝ. ΣΥΣΚΕΥΑΣΙΑ
MASTER PACKING

X3030S 3000K 2500Lm	12
X3040S 4000K 2580Lm	12
X3060S 6000K 2660Lm	12





X50**S

"X" 50W 120° 230V

ΓΕΝ. ΣΥΣΚΕΥΑΣΙΑ
MASTER PACKING

X5030S 3000K 4000Lm	12
X5040S 4000K 4100Lm	12
X5060S 6000K 4180Lm	12




EPISTAR




MAYPO
BLACK


- Σώμα χυτού αλουμινίου για ιδανική απαγωγή της θερμότητας / Die-casting aluminum body for ideal heat dissipation.
- Διαφανές πυρίμαχο γυαλί 5mm / Clear fire-resistant 5mm glass.
- Ανταυραστήρας αλουμινίου υψηλής καθαρότητας / High-purity aluminum reflector.
- Αισθητήρας κίνησης με 50.000 on-off / Motion sensor with 50.000 on-off.
- 12 μέτρα μέγιστη εμβέλεια ανίχνευσης / 12m maximum detected range.
- 4 μέτρα μέγιστο ύψος ανίχνευσης / 4m maximum detected height.
- Δυνατότητα ρύθμισης χρόνου / Ability of time adjusting (10sec - 4min).
- Δυνατότητα ρύθμισης ευαισθησίας / Ability of sensitivity adjusting (10-20,000Lux).
- Θερμοκρασία λειτουργίας -15°~+50°C / Operating temperature -15°~+50°C.




X10**S



X20**S



X30**S



X50**S

ΣΕ ΠΑΡΑΓΓΕΛΙΑ ΓΕΝ. ΣΥΣΚΕΥΑΣΙΑΣ ΕΠΙΠΛΕΟΝ ΕΚΠΤΩΣΗ 5%
FOR MASTER PACKING ORDER EXTRA DISCOUNT 5%