

## NYMPHEA plafond



---

|                |                       |                           |              |
|----------------|-----------------------|---------------------------|--------------|
| Power          | <b>36 W</b>           | Voltage                   | <b>230 V</b> |
| Luminous flux* | <b>2840 lm (120°)</b> | Colour of light           | <b>CCT</b>   |
| Beam angle     | <b>120 °</b>          | Degree of protection (IP) | <b>IP20</b>  |

---



 User manual





 Declaration of Conformity



 Photometric file

## Technical data:

|                                   |                |
|-----------------------------------|----------------|
| Code                              | SLI031032CCT   |
| Power                             | 36 W           |
| Nominal current                   | 165 mA         |
| Voltage                           | 230 V          |
| Energy efficiency class           | F              |
| Energy consumption                | 36 kWh/1000h   |
| Frequency                         | 50HZ Hz        |
| Protection class                  | I              |
| Power supply included             | +              |
| Power factor                      | 0.9            |
| Luminous flux*                    | 2840 lm (120°) |
| Luminous flux**                   | 2840 lm (360°) |
| Lamp efficacy                     | 79 lm/W        |
| Colour of light                   | CCT            |
| Beam angle                        | 120 °          |
| RA                                | 80             |
| Light source included             | +              |
| Uniformity of color SDCM max      | 5              |
| Dimmable                          | SMART          |
| Working temperature range         | -20/+40 °      |
| Lifespan                          | 17000 h        |
| Housing material                  | PC             |
| Degree of protection (IP)         | IP20           |
| Colour                            | White          |
| Dimension (AxBxC)                 | 488x72 mm      |
| Weight                            | 1.87 kg        |
| For use                           | Inside         |
| Assembly                          | On the ceiling |
| Application                       | INT            |
| Number of pieces on the packaging | 5 pcs.         |
| Made in                           | PRC            |



\*applies to the LED source used. \*\*Luminaire luminous flux