

## FIALE 3 STEPS spotlight




CE

---


Power	<b>5,5 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>490 lm (120°)</b>	Colour of light	<b>NW</b>
Beam angle	<b>120 °</b>	Degree of protection (IP)	<b>IP20</b>

---



 Declaration of Conformity



 Photometric file

**Technical data:**

Code	SLI022025NW
Power	5,5 W
Nominal current	46 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	6 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.5
Luminous flux*	490 lm (120°)
Luminous flux**	490 lm (360°)
Lamp efficacy	89.1 lm/W
Colour of light	NW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	83x40 mm
Mounting hole	66 mm
Weight	0.1 kg
For use	Inside
Assembly	In the ceiling
Application	INT
Number of pieces on the packaging	20 pcs.
Made in	PRC



\*applies to the LED source used. \*\*Luminaire luminous flux