


LED CEILING LAMPS WITH SENSOR

Ultralux®




LED PIR CEILING LAMP, ROUND


Product No.	Voltage	Power	Colour temperature	Luminous flux	Cat. No.
SPLP1642	220 - 240 V AC	16 W	4200 K	1150 lm	11162



Housing: ABS
Diffuser: PC
Adjustable time delay
and ambient light threshold.




Detection distance: max. 3 m
Mounting height: 2.2-4.0 m
Ambient light threshold: 3-2000 lx
Time delay: 10 sec-3 min




LED CEILING LAMP WITH MICROWAVE SENSOR, ROUND


Product No.	Voltage	Power	Colour temperature	Luminous flux	Cat. No.
SPLS1240	220 - 240 V AC	12 W	4000 K	800 lm	11117



Housing: Powder coated steel
Diffuser: PVC
Adjustable time delay, ambient light threshold
and detection distance.




Detection distance: 2-8 m
Mounting height: 1.5-3.5 m (wall mounting), 2-8 m (ceiling mounting)
Ambient light threshold: 10-2000 lx
Time delay: 5 sec-10 min




LED CEILING LAMP WITH MICROWAVE DIMMING SENSOR, SQUARE

Product No.	Voltage	Power	Colour temperature	Luminous flux	Cat. No.
SPLM1240D	220 - 240 V AC	12 W	4000 K	850 lm	11143



Housing: PBT
Diffuser: PC
Adjustable Time delay,
ambient light threshold
and detection distance.
2 dimming levels: 10% / 20%
Soft dimming function



Detection distance: 5-15 m (wall mounting), 2-8 m (ceiling mounting)
Mounting height: 1.5-3.5 m (wall mounting), 2-4 m (ceiling mounting)
Detection range: 180°/360°
Ambient light threshold: 5/15/50/2000 lx
Operating time at full power: 10 sec/90 sec/3 min/10 min

