

SLI044021NW



Power	190 W	Voltage	230 V
Luminous flux*	20400 lm (90°)	Colour of light	NW
Beam angle	90 °	UGR	- lm
IK	09	Degree of protection (IP)	IP66



 [User manual](#)





 [Declaration of Conformity](#)



 [Photometric file](#)

Technical data:

Code	SLI044021NW
Power	190 W
Nominal current	840 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	190 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.9
Luminous flux*	20400 lm (90°)
Luminous flux**	18000 lm (360°)
Lamp efficacy	95 lm/W
Luminous intensity	9300 cd
Colour of light	NW
Beam angle	90 °
UGR	-
RA	>80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	Aluminum
IK	09
Degree of protection (IP)	IP66
Colour	Black
Dimension (AxBxC)	353x114 mm
Weight	2.15 kg
For use	Inside/Outside
Assembly	Pendant
Application	Inside/Outside
Number of pieces on the packaging	6 pcs.
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux