




LED CEILING LAMP, ROUND

Product N°	Voltage	Power	Colour temperature	Luminous flux	Cat. N°
LBH1542R	220 V-240 V AC	15 W	4200 K	1100 lm	11121



Housing: PC
Diffuser: PC



- IP44** IP RATE
- 240V 220V** VOLTAGE
- 50/60Hz** FREQUENCY
- 120°** BEAM ANGLE
- Ra ≥ 80** CRI
- SMD** LED TYPE
- ON OFF** x 15 000
- ON** <0.2 sec.
- ON 100%** INSTANT

CEILING LAMPS



LED CEILING LAMP, SQUARE

Product N°	Voltage	Power	Colour temperature	Luminous flux	Cat. N°
LBH1542S	220 V-240 V AC	15 W	4200 K	1100 lm	11122





Housing: PC
Diffuser: PC

- IP44** IP RATE
- 240V 220V** VOLTAGE
- 50/60Hz** FREQUENCY
- 120°** BEAM ANGLE
- Ra ≥ 80** CRI
- SMD** LED TYPE
- ON OFF** x 15 000
- ON** <0.2 sec.
- ON 100%** INSTANT



LED CEILING LAMP, ROUND

Product N°	Voltage	Power	Colour temperature	Luminous flux	Cat. N°
LBH1442BL	220 V-240 V AC	14 W	4200 K	1000 lm	11123



Housing: PC
Diffuser: PC

- IP44** IP RATE
- 240V 220V** VOLTAGE
- 50/60Hz** FREQUENCY
- 120°** BEAM ANGLE
- Ra ≥ 80** CRI
- SMD** LED TYPE
- ON OFF** x 15 000
- ON** <0.2 sec.
- ON 100%** INSTANT