





DECORATIVE LED CEILING LAMP, ROUND



Powder coating steel sheet
Diffuser: PVC



Product Nº	Voltage	Power	Colour temperature	Luminous flux	Cat. Nº
SPLD1827	220 V-240 V AC	18 W	2700 K	1200 lm	11108
SPLD1840	220 V-240 V AC	18 W	4000 K	1200 lm	11109

- VOLTAGE**: 240V / 220V
- FREQUENCY**: 50/60Hz
- BEAM ANGLE**: 120°
- IP RATE**: IP20
- CRI**: Ra ≥ 80
- LED TYPE**: SMD
- ON/OFF**: x 15 000
- ON/OFF**: <0.2 sec.
- ON/OFF**: INSTANT

CEILING LAMPS



DECORATIVE LED CEILING LAMP, ROUND





Powder coating steel sheet
Diffuser: PVC

Product Nº	Voltage	Power	Colour temperature	Luminous flux	Cat. Nº
SPLD1227	220 V-240 V AC	12 W	2700 K	800 lm	11110
SPLD1240	220 V-240 V AC	12 W	4000 K	800 lm	11111

- VOLTAGE**: 240V / 220V
- FREQUENCY**: 50/60Hz
- BEAM ANGLE**: 120°
- IP RATE**: IP20
- CRI**: Ra ≥ 80
- LED TYPE**: SMD
- ON/OFF**: x 15 000
- ON/OFF**: <0.2 sec.
- ON/OFF**: INSTANT



LED CEILING LAMP, ROUND



Powder coating steel sheet
Diffuser: PVC

Product Nº	Voltage	Power	Colour temperature	Luminous flux	Cat. Nº
SPL1227	220 V-240 V AC	12 W	2700 K	800 lm	11112
SPL1240	220 V-240 V AC	12 W	4000 K	800 lm	11100

- VOLTAGE**: 240V / 220V
- FREQUENCY**: 50/60Hz
- BEAM ANGLE**: 120°
- IP RATE**: IP20
- CRI**: Ra ≥ 80
- LED TYPE**: SMD
- ON/OFF**: x 15 000
- ON/OFF**: <0.2 sec.
- ON/OFF**: INSTANT