

Caracteristici Produs

- Camera IP 5 Megapixeli
- Solutie SONY Starvis Back-illuminated IMX335
- Compresie H.265 / H.264 / JPEG / AVI / MJPEG
- Lentila varifocala (2.7-13.5)mm
- **ZOOM MOTORIZAT 5X** si AUTO-FOCUS
- Alimentare 12V DC, POE integrat



Camera IP 5Megapixeli / IR 40M ESVZ5M/5X

Specificatii tehnice:

Model	ESVZ5M/5X
Senzor Imagine	SONY Starvis Back-illuminated IMX335
Rezolutie efectiva	2592 x1944
Obturator Electronic	1 / 25 s ~ 1 / 100000 s
Illuminare Minima	0.01 lux @F1.2, AGC ON; 0 lux with IR
Lentila	Varifocala Motorizata (2.7-13.5) mm – ZOOM 5X
PoE	Integrat
ZI / NOAPTE	ICR
WDR	Digital WDR
3DNR	2D / 3D DNR
Defog	Da
Image	
Video Compression	H.265 / H.264 / JPEG / AVI / MJPEG
Sistem Scanare	Progresiv
Rezolutie	5 MP(2592*1944)
Stream principal	2592*1944@20fps; 2560*1920@20fps;
Bit rate	64 Kbps ~ 8 Mbps

Mod codare	VBR / CBR
Calitate	5 niveluri de calitate selectabile
Setari Imagine	ROI. Saturation. Brightness. Chroma. Contrast. Wide Dvynamic. Defoq

Interfata	
Retea	RJ45, 10M / 100M self-adaptive
Audio	Optional
Iesire video analogica	Optional
Funcții	
Monitorizare	Internet Explorer, CMS, Aplicatie Android / iPhone
Conectare Online	Maxim 10 utilizatori simultani
Protocol	TCP / IP, UDP, DHCP, NTP, RTSP, DDNS, SMTP, FTP
Protocol Interfata	ONVIF 2.4
Stocare	In retea
Alarmer	Detectie la miscare
PoE	Optional
Vedere pe timp de noapte	40M
Protectie	IP67
Altele	
Alimentare	DC 12V / optional PoE
Consum	1000mA
Temperatura Operare	- 30 °C ~ 66 °
Dimensiuni	162 × 88 x 86
Greutate	600g

