TECHNICAL DATASHEET

TOPTOUCH PLUS NITRIL ULTRASOFT

SINGLE USE DISPOSABLE NITRILE EXAMINATION GLOVES

CONFIGURATION OVERVIEW

Shape: Ambidextrous and Finger textured
Material: Nitrile
Type: Non Sterile
Powder Free
Colour: White

TECHNICAL SPECIFICATIONS

Thickness:

Location of Thickness Measurement	Single Wall (mm)	
	ASTM D6319	AKZENTA
Finger	Min 0.05	Min 0.09
Palm	Min 0.05	Min 0.05
Cuff	N/A	Min 0.05

Physical Properties:

	ASTM D6319	AKZENTA
Tensile Strength (MPa)	Min. 14	Min. 14
Elongation (%)	Min 500	Min 400
Force Break (N)	N/A	Min. 6

Residual powder: Max. 2 mg/glove
Length: Median 240 mm

QUALITY ASSURANCE

Quality certification: ISO 9001, certified by SGS (UK) and SIRIM (Malaysia)
ISO 13485 certified by SGS (UK)
CMDCAS ISO 13485 certification

Inspection Criteria (Sampling & Inspection ISO 2859): Watertight Test (G1, AQL 1.5), Major Defects (G1, AQL 2.5), Minor Defects (G1, AQL 4.0)
Dimensions (S2, AQL 4.0), Physical Properties (S2, AQL 4.0)

Conformity to standards: ASTM D6319, EN 455 Part 1, 2, 3 & 4

Sizes	XS	S	M	L
Art-No.	**NITR2S-AZ-W-XS**	**NITR2S-AZ-W-S**	**NITR2S-AZ-W-M**	**NITR2S-AZ-W-L**

PACKAGING

Pcs/Dispenser: 100 **Dispenser/Carton:** 10
Carton Size: 27x25,5x24,5cm
Carton weight: XS: 3.5 Kg – S: 3.7 kg – M: 3.9 Kg - L: 4.1 Kg
Carton / layer: 12 **Layer / pallet:** 7
Carton / pallet: 84 **Pallet size:** cm 80x120x187