

**FERASTRAU PENDULAR**

- Putere: 800 W • Ghidaj de taiere cu fascicul laser • Sistem prindere cu un imbus • 3 trepte de pendulare • Turatie variabila • Talpa de fixare metalica • Reglaj unghi de taiere pana la 45° • Taie in lemn pana la 80 mm adancime • Maner ergonomic, aderent

**DATE TEHNICE**

Tensiune/Frecventa: 230 V ~ 50 Hz

**Putere motor: 800 W**

Turatie mers in gol: 500-3000 rot/min

Adancime taiere (lemn): 80 mm

Adancime taiere (metal): 10 mm

Gradul de inclinare: 0°-45°

**Trepte de oscilatie: 0, I, II, III**

Nivel zgomot in gol: 87.0 dB(A)

Nivel zgomot in sarcina: 92.0 dB(A)

Nivel de vibratii:

ah,B= 6.38 m/s<sup>2</sup> K B = 1.5 m/s<sup>2</sup>


ah,M= 6.02 m/s<sup>2</sup> K M = 1.5 m/s<sup>2</sup>

Clasa protectie: II

Buc./carton: 10

Greutate neta: 2.28 kg

Greutate bruta: 2.60 kg

**800W****500-  
3000/min****80mm  
(lemn)****10mm  
(metal)****45° 0° -45°****MANER  
ADERENT**