

CLEACON VIS-DVU-FS2

Digital Voting Unit



Features

- Flushing-mounting, stylish, low profile design with touchable interface
- Max system capacity: 3000 voting units
- 5 voting keys
- Plug and play

Functions

- Anti 8kV static, conforms to IEC CISPR 24
- 5 voting buttons with the red back-light confirmation indicators to prompt the users to indicate presence, to vote and to confirm registration of what is voted. The buttons and indicators work as follows:
 - Yes(+),no(-) and abstain(x)(For/against, parliamentary voting)
 - Numerals 1 to 5(Used for multiple choice, option polls and rating)
 - Rating scale:--,0,+,++(used for audience response)
- Use the PC software to support more voting form
- Max. system capacity:3000 voting units
- Key-press sign-in
- Automatic detection

Control & Indicators

Five touch-buttons for voting
One LED sign-in indicator

Interfaces

No.1. RJ11 socket for VIS-CSU-F or VIS-DCC-F/
VIS-DCD-F

No.2 RJ11 socket for VIS-DCC-FS/VIS-DCD-FS

Technical Parameters

Mounting: Flush-mounting

Weight: 0.1kg

Dimension: 100W × 40H × 30H mm

Operating temperature: 0 °C to + 55 °C

Color: Black

Item Model for Order

VIS-DVU-FS2..... Digital Voting Unit
VIS-DCC-F..... Digital Flush-mounting
Discussion Chairman Unit, microphone and cable not
include
VIS-DCD-F..... Digital Flush-mounting
Discussion Delegate Unit, microphone and cable not
include
VIS-CSU-F..... Digital Flush-mounting 64
Channel Selector