

# Vorreiniger Power-Clean SC 16000

universal cleaning and degreasing – super concentrate

**Characteristics:**

Combines, high strongly foaming cleaning power with inhibitor-protection. Removes dirt like liquid oil, fat, insect residues, exhaust fumes, and other road dirt. Excellent for the cleaning of HGV, tank lorries, busses, containers, bashes, vehicle superstructures, plastic surfaces, facades, work shops, floors, petrol pumps, machines and tools. Suitable for metal, lacquer, glass, plastics and ceramic. If applied with the help of a foaming spear or cannon, outstanding cleaning results can be achieved. Improves the colour intensity of plastic and rubber parts. Does not leave traces if applied properly. The regular use of Pre-Cleaner Power Clean facilitates the cleaning in subsequent applications.

**Application:**

Only use diluted. Warmed-up lacquers and ornamental mouldings etc have to be rinsed with cold water before application. Do not let dry out on lacquered or delicate surfaces! Do not applied in direct sunlight, on hot or delicate lacquer or ornamental mouldings; but only on cold supports and lacquered surfaces.

Spay-gadgets:	Depending on the soiling dilute 1:20 to 1:60
High-pressure-appliances:	Depending on the dosage installation dilute 1:1 to 1:10 .
Manual cleaning	1:40 to 1:100

**Technical facts:**

Appearance:	Yellow
Density:	1,09 g/cm <sup>3</sup>
pH-factor (10 g/l):	11,6
Flash point:	51 °C
Odour	lemony

**Important ingredients:**

Ingredient information according to EEC – recommendations (89/542/EWG): 5 - 15 % NTA, < 5 % anionic tensides, < 5 % non-ionic tensides, < 5 % cationic tensides, < 5 % phosphates, further ingredients: Alkali hydroxides, silicates, Carbonates,

When using these products, all applicable safety regulations for the use of chemicals must be observed. For storage information, danger specifications, and safety regulations, please refer to the applicable safety data sheets. Application solutions and product remnants must be discarded in compliance with official regulations. The information given reflects our previous experience. With regard to varying operational conditions, this information is noncommittal and to be used as advice only. Therefore, we assume no liability whatsoever, including claims from third parties.

## TECHNICAL INFORMATION



dissolving agents, water miscible solution agent, odoriferous agent and colouring. Free of absorbable organic halogen compounds (AOX). Does not contain any organic complex builders that will not reach a DOC elimination degree of min. 80% after 28 days.

- Material sociability:** Test for material sociability in an inconspicuous area.
- Security:** Please consult our security fact sheet for danger specification and security advice relating to the use of this product.
- Waste water conduct:** If used for the intended purpose the functioning of the oil separator is not affected. Pre-cleaner Power-Clean is suitable for the use in water-regeneration installations.  
The applied tensides are biodegradable according to WRMG .

UBA - 34620216

When using these products, all applicable safety regulations for the use of chemicals must be observed. For storage information, danger specifications, and safety regulations, please refer to the applicable safety data sheets. Application solutions and product remnants must be discarded in compliance with official regulations. The information given reflects our previous experience. With regard to varying operational conditions, this information is noncommittal and to be used as advice only. Therefore, we assume no liability whatsoever, including claims from third parties.

15.05.2007 Page 2 of 2