

TECHNICAL DATA SHEET

UA-EAGLE (SW63-20/55)55%

Long oil polyurethane alkyd resin based on Soya oil or Sunflower oil

Delivery forms:

It's available at 55 ±1% in W.Spirit



EAGLE CHEMICALS™

Performance	Dilutability	Soluble	Limited	Insoluble
<ul style="list-style-type: none">Light color with good yellowing resistanceVery high abrasion resistanceFast drying timeVery good compatibility with the majority medium & long air drying alkyds	<ul style="list-style-type: none">Aliphatic hydrocarbonAromatic hydrocarbonChlorinated hydrocarbonAlcohols Ketons	<ul style="list-style-type: none">+++- +	<ul style="list-style-type: none">---- -	<ul style="list-style-type: none">---+ -

Suggested uses

- Varnish for parquet floor
- Pigmented decorative enamels for interior use only
- Furniture finishes & Yacht varnishes
- Wood varnishes

Composition		Application	
<ul style="list-style-type: none">Type of isocyanateFree isocyanate contentType of oilOil %Type of Polyol	<ul style="list-style-type: none">Aromatic0 %Soya63Penta	<ul style="list-style-type: none">AirBakeNitrocelluloseCatalyze	<ul style="list-style-type: none">+---

Specification		Storage Conditions
<ul style="list-style-type: none">Viscosity Gardner at 25°C (55%)Viscosity C-poise at 25°C (55%)Acid value mg KOH/gm solidColor Gardner	<ul style="list-style-type: none">Y-ZApprox.20002 Max.5 Max.	UA-EAGLE (SW63-20/55) should be stored indoors in the original, unopened and undamaged containers in a dry Place at storage temperatures between 5°C&30°C. Exposure to sun shine should be avoided.

Stability

Under the above-mentioned storage conditions the Stability of UA-EAGLE (SW63-20/55) will be 24 months ex-work

** Pls test the drying time after 48hours from adding the driers to the paint (min. 24 hours)